

Product Description

The OGOS S10 is a compact 2-way Line Source Speaker. It contains one 10" Ferrite Cone Driver and one 3" Compression Drivers, mounted on a Linearray Waveguide with Constant Coverage Horn.

For convenient and safe stacking (up to 4 cabinets) and polemount use (up to 2 cabinets) is a mounting frame with M20 adapter available.

For bass extensions it is recommended to use the BR115 or BR115A, which share the same width and therefore able to be combined with the OGOS S10 in homogen and compact combinations.



Technical Data

Description:	2-way Line Source
Transducers:	LF: 1x 10" , Bassreflex Loaded HF: 1x 3" Compression Driver, 1.4" Exit
Frequency Range (-10dB) ¹ :	50Hz - 18kHz
Sensitivity (1W/1m):	96dB
Power Handling RMS ² :	300W
Nominal Impedance:	16Ω
Coverage (-6dB):	90° x 10° conical
Connectivity:	2x SPEAKON NL4 type
Rigging:	with flyframe up to 12 cabinets
Dimensions (WxDxH):	550mm x 445mm x 285mm
Weight:	24kg



¹ with G-ACOUSTIC processor setup in fullrange mode

² with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

